

Zertifikat

mit überwachter Konformität

Certificate

of surveyed conformity



Zertifikat Nr. *Certificate No.*
J 50466412

Blatt *Sheet*
0001

Ihr Zeichen *Client Reference*

Unser Zeichen *Our Reference*

Ausstellungsdatum

Date of Issue

05-YFC-50298394 001

29.05.2020

(day/mo/yr)

Genehmigungsinhaber *License Holder*

DONGGUAN REOMAX ELECTRONICS
TECHNOLOGY CO., LTD.

Ditangling Industrial Park, Datang
Village, Dalingshan Town, Dongguan
523800 Guangdong
P.R. China

Fertigungsstätte *Manufacturing Plant*

DONGGUAN REOMAX ELECTRONICS
TECHNOLOGY CO., LTD.

Ditangling Industrial Park, Datang
Village, Dalingshan Town, Dongguan
523800 Guangdong
P.R. China

Prüfzeichen *Test Mark*



Geprüft nach *Tested acc. to*

EN 60127-1:2006+A1+A2

EN 60127-3:2015

Zertifiziertes Produkt (Geräteidentifikation)

Certified Product (Product Identification)

Lizenzentgelte - Einheit

License Fee - Unit

(Sub-miniature Fuse-links)

Type Designation	: 96T 96F	6
Trademark	: REOMAX REOMAX (logo)	
Rated Voltage	: AC 250V/500V; DC 250V/500V	
Time/Current Characteristic	: T	
Rated Breaking Capacity	: 100A	
Rated Current (In)	:	9
125mA; 160mA; 200mA; 250mA; 300mA; 315mA; 350mA; 400mA; 500mA; 630mA; 750mA; 800mA; 1A; 1,25A; 1,5A; 1,6A; 2A; 2,5A; 3A; 3,15A; 3,5A; 4A; 5A; 6A; 6,3A; 7A; 8A; 10A; 12A; 15A; 16A; 20A; 25A; 30A		

Remark: The requirements of standard sheet 4 were taken into consideration.

The labelling requirements acc. to EU Directive 2001/95 have to be observed for distribution within the EEA.

15

ANLAGE (Appendix): 1

Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product fulfills above mentioned requirements, the production is subject to surveillance.

TÜV Rheinland LGA Products GmbH, Tillystraße 2, 90431 Nürnberg

Tel.: +49 221 806-1371 e-mail: cert-validity@de.tuv.com

Fax: +49 221 806-3935 http://www.tuv.com/safety



DONGGUAN REOMAX ELECTRONICS
TECHNOLOGY CO., LTD.
Tang Liang

Date : 29.05.2020
Our ref. : YFC 05
Your ref.:

Ditangling Industrial Park, Datang
Village, Dalingshan Town, Dongguan
523800 Guangdong
P.R. China

Ref : J Certificate of Surveyed Conformity

Type of Equipment : Sub-miniature Fuse-links
Model Designation : See Certificate
Certificate No. : J 50466412 0001
Report No. : 50298394 001

Dear Tang Liang,

The above specified technical equipment has been tested and found to be in accordance with the relevant requirements.

Enclosed you will find the certificate of approval.

If cancellation of the certificate is submitted by November 15 in a given year, no fee will be charged for the following year.

We appreciate your kind support and would like to offer our assistance and continuous services in the future.

Please contact our office for approval of your new products.

With kind regards,

Certification Body

G. Yin

Enclosure

证书的详细资料请登陆www.tuvdotcom.com查阅,或拨打我司客服热线800 999 3668 / 400 883 1300咨询

Constructional Data Form (CDF) for Sub-miniature Fuse-links

License holder	:	DONGGUAN REOMAX ELECTRONICS TECHNOLOGY CO., LTD. Ditangling Industrial Park, Datang Village, Dalingshan Town, Dongguan, 523800 Guangdong, P.R. China
Factory	:	DONGGUAN REOMAX ELECTRONICS TECHNOLOGY CO., LTD. Detangling Industrial Park, Dating Village, Dalingshan Town, Dongguan, 523800 Guangdong, P.R. China
Kind of device	:	Sub-miniature Fuse-links
Type designation	:	96T; 96F

Type Designation	96T; 96F	
Rated Current (I _N)	125mA; 160mA; 200mA; 250mA; 300mA; 315mA; 350mA; 400mA; 500mA; 630mA; 750mA; 800mA; 1A; 1,25A; 1,5A; 1,6A; 2A; 2,5A; 3A; 3,15A; 3,5A; 4A; 5A; 6A; 6,3A; 7A; 8A; 10A; 12A; 15A; 16A; 20A; 25A; 30A	
Rated Voltage (U _N)	AC 250V/300V/350V/400V/500V	DC 250V/300V/350V/400V/500V
Rated Frequency	50Hz / 60Hz	--
Rated Breaking Capacity	100A	100A
Standard sheet	4	
Normal ambient temperature	15°C-35°C	
Time/Current Characteristics	T	
Maximum Rated Power Dissipation	See appended table	
Maximum Voltage drop (measured at 20°C ambient temperature at rated current)	See appended table	
Cut-off Current Characteristics	--	
I ² t Characteristics	--	
Dimensions	See dimension drawing	
Termination material	Tin plated copper	
Solder type(1 or 2) according to IEC68-2-20	1	

Part Name	Material Name	PTI minimum	Flame Class	Material Group
Inner core / Case	HFPA66-RPG25 (UL approval: E171666, manufacture: KINGFA SCI & TECH CO LTD)	--	V-0	--
Fuse-link element	Tin plated copper or sliver	--	--	--
Lead wire	Tin plated copper	--	--	--
Filler	Silica	--	--	--

